



AQSYNC AIR QUALITY MONITORING STATION

The Best of the Best in One Package

- 2B Tech's High Precision FEM Instruments for O_3 , NO_2 and NO
- FEM Quality Instrument for PM_{10} , $PM_{2.5}$, PM_{10}
- Reliable Measurements for CO_2 , CO , and tVOCs
- Meteorological Station Including Sonic Anemometer
- Data Access and Instrument Control via the Cloud



BRING IT ALL TOGETHER WITH THE AQS SYNC

- ✓ FEM absorbance measurements for O_3 , NO_2 and NO
- ✓ Optical particle counter with sheath flow and heated inlet for PM_{10} , $PM_{2.5}$, $PM_{1.0}$
- ✓ Photoionization for total VOCs
- ✓ Amperometry for CO
- ✓ NDIR absorbance for CO_2
- ✓ Power stingy requirements enable options for powering with battery or solar panel

ONE DEVICE
TO DO THE WORK...

OF ALL OF THESE.



Myriad Electronic Solutions Inc. d.b.a. ES Canada
422 Richard St, Vancouver, BC V6B 2Z4



Tél. 778-652-2717



e-mail : info@es-canada.com
Site Web : www.es-canada.com

SPECIFICATIONS AND FEATURES

Measurements	O ₃ (FEM), NO ₂ (FEM), NO, PM ₁ , PM _{2.5} , PM ₁₀ , tVOCs, CO, CO ₂ , T, P, RH, wind speed, wind direction
Operation	Touchscreen or remotely via the Web
Data Transmission	Cellular, WiFi, Ethernet, Modbus (TCP), SD card
Power Requirements	120/240 VAC or 12 V DC, solar ready
Enclosure	Rugged NEMA 4X, IP67
Dimensions	25.5" H x 25.5" W x 10.3" D (with weather station, height is 49")
Weight	54.7 lb (dependent on modules chosen)

EXPAND POSSIBILITIES

- Place a network of AQSyncs at public sites to increase community monitoring
- Use the AQSync to calibrate sensor networks
- Extend air quality monitoring to sparse data areas or remote locations
- Quickly deploy reliable instrumentation for forest fires or other emergency response
- Utilize the AQSync on a solar trailer for road-side monitoring during construction



2B Technologies | +1-303-273-0559 | www.twobtech.com
6800 W. 117th Ave., Broomfield, Colorado 80020, USA