

# WPF60 Probe

## 1 MHz – 60 GHz




- Electric field measurement
- Isotropic & True RMS measurement
- High dynamic range of 60 dB
- Excellent attenuation at 50/60 Hz
- Measurements in accordance with International Standards

1 MHz - 60 GHz

E

RMS

ISOTROPIC



**Telecommunications**  
Certification and audit of telecommunication services (GSM, 3G, LTE, TDT, FM, WiFi, etc.).



**Industry**  
Assessment of industrial processes for worker's exposure protection



**Radar/Aerospace**  
Assessment of radar and aerospace sites and personnel exposure protection.



**Labs/R&D**  
RF exposure protection of R&D and labs personnel.



### Technical Specifications

	WPF60	WPF60 FAST
Part Number	WWP2301	WWP2311
Frequency range	1 MHz - 60 GHz	
Sensor type	Isotropic RMS diode technology	
Type of frequency response	Flat	
Measurement range	1 – 1000 V/m (CW) 1 – 55 V/m (True RMS)	
Dynamic range	60 dB	
Sensitivity	1 V/m	
Integration time	500 ms	4 ms
Frequency response (*)	± 2 dB (2 MHz – 17 GHz) ± 3 dB (17 GHz – 40 GHz) ± 6 dB (40 GHz – 60 GHz) - 3 dB @ 1 MHz	
Linearity	± 2 dB (1 – 2 V/m) ± 1 dB (2 – 250 V/m)	
Isotropic deviation	± 1.1 dB (< 12 GHz) ± 2.2 dB typ. (12 GHz to 60 GHz)	
Damage level (CW)	1200 V/m	
Calibration	ISO 17025 Accredited Calibration (ILAC)	
Calibration period	24 months (recommended)	
Temperature range	- 20 °C to 50 °C	
Temperature response	+ 0.1 / - 1 dB (related to 20 °C)	
Dimensions	28.4 cm x 6 cm Ø	
Weight	95 g	
Attenuation at 50/60 Hz	> 40 dB	

(\*) The frequency response can be corrected with the SMP2/SMP3 by using the correction factors stored in the probe (ISO 17025 accredited calibration).

Compatible with **SMP3**, **SMP2**, **MonitEM**, **MapEM**



WPF60\_EN\_2601\_V1.4