

INDUSTRY WIND DIRECTION SENSOR



A very economical purchase

Of a special nature and a very economical purchase is this wind direction sensor. Furthermore, the sensor impresses with high accuracy, the simplest mounting methods and ultimately robust, seawater resistant materials. The optimal heating of the sensor head and the minimum power demand of the system are made possible by thermal decoupling of the housing shaft.

- precision, tradition and future reliability
- large operative measuring and temperature range
- simplest mast mounting
- very good starting values through magnetic, contactless measuring principle
- optimal heating concept

APPLICATIONS

- industrial applications
- wind power plants
- building services
- wind warning devices on cranes
- in all climatic zones
- environmental measurements

Professional Line	INDUSTRY
Id-No.	00.14567.110040 Wind direction 4...20 mA output
Measuring range	0...360°
Accuracy	± 2°
Resolution	2°
Starting value	0.7 m/s
Output	4...20 mA 0...20 mA and 0...10 V on request max. load 600 Ω
Range of application	temperatures -30...+70 °C heated; wind speed 0...60 m/s
Supply voltage	24 (20...28) VDC; max. 800 mA; electr. controlled heating; 18 W
Measuring elements	plastic • wind vane - dimensionally stable
Measuring principle	Hall Sensor Array
Dimensions	wind vane L 232 mm - H 327 mm
Housing	aluminium anodised; IP 55; Ø 32 mm; bore Ø 30 mm for mounting at traverse
Weight	approx. 0.35 kg
Accessories (order separately)	32.14567.060000 Sensor cable 12 m

As of: 19.01.2023

LAMBRECHT meteo GmbH Tel +49 (0) 551-4958-0 · info@lambrecht.net · www.lambrecht.net