

Automatic Pineapple Peeler KA-750PM Spec Sheet

Model		KA-750PM	
Size		210mm(W) × 385mm(D) × 500mm(H) *Main unit only	
Weight		13kg(Main unit)、15kg(Including option parts)	
Power Supply		AC100-240V 50/60Hz (3P grounding-type plug)	
Power Consumption		250W (max) / 5W (standby mode)	
Performance	Use for	Pineapple, Melon, Mango, Pumpkin (Kent)	
	Fruit size	Pineapple: height100-170mm (diameter: 60-160mm) Melon: height 130-220mm (diameter: -180mm) Mango: height100-160mm Pumpkin (Kent) : height 80-150mm(diameter: -200mm)	
	Process time	Pineapple: 7.5 / minute, not including loading time	
	Continuous operation	Unlimited (10 minutes interval recommended every 2 hours)	
	Inspection	Required (by metal detection)	
Environment	Temperature, humidity	0-40°C under 85RH%	
	Water/dust proof	IP54 equivalent (except for the back and bottom)	
	Cleaning	Body	Flow water, shower (high pressure cleaning not possible)
		Arm	Washable (dishwasher, alcohol, hypo-water available)
Prongs		Washable (dishwasher, alcohol, hypo-water available)	
Material		SUS303/304/304WPB/420J2(Blade)/430/440/ POM	
Maintenance		Wash it at least once per day when in use. Check that all parts are functioning correctly.	
Warranty		One year from purchase or within 1,000 hours of total usage time	
Inspection conditions		After completion of installation and operation, check	